

# DRIVES

## PRODUCT OVERVIEW

**servotecnica**

BLDC Motors, DC Motors

Operating voltage 9-60Vdc

Operating temperature: -25 +70°C

Model	Current Nom/Peak	Feedback				Fieldbus			Vdc Out	I/O (Dir/Dout/Ain)
		HALL	TTL		SIN/COS	CANbus	EtherCAT	Profinet		
			Single Ended	Line Drive						
 SVTE-A-B40-CanOpen*	10/30	•				•			90%	4/0/1
 SVTE-A-E25-CanOpen*	35/100	•	•	•		•			100%	8/2/2
 SVTE-A-E25-EtherCAT	35/100	•	•	•		•	•		100%	8/2/2
 SVTE-A-E40-CanOpen*	10/30	•	•	•		•			90%	4/1/1
 SVTE-A-E40-EtherCAT	10/30	•	•	•		•	•		90%	4/1/1
 SVTE-A-E45-CanOpen*	10/50	•	•	•		•			100%	8/2/2
 SVTE-A-E45-EtherCAT	10/50	•	•	•		•	•		100%	8/2/2
 SVTE-A-E45-Profinet**	10/50	•	•	•		•		•	100%	8/2/2
 SVTE-A-E47-CanOpen*	10/50				•	•			100%	7/2/2
 SVTE-A-E47-EtherCAT	10/50				•	•	•		100%	7/2/2
 SVTE-A-E50-CanOpen*	7.5/25	•	•			•			90%	8/4/3
 SVTE-A-E55-CanOpen*	10/50	•	•	•		•			100%	8/4/3
 SVTE-A-E55-EtherCAT*	10/50	•	•	•		•	•		100%	8/4/3
 SVTE-A-E55-Profinet*	10/50	•	•	•		•		•	100%	8/4/3
 SVTE-A-E57-CanOpen*	10/50				•	•			100%	8/4/3
 SVTE-A-E50-HC-CanOpen*	14.5/25	•	•			•			90%	8/4/3
 SVTE-A-E55-HC-CanOpen*	14.5/50	•	•	•		•			100%	8/4/3
 SVTE-A-E55-HC-EtherCAT*	14.5/50	•	•	•		•	•		100%	8/4/3
 SVTE-A-E55-HC-Profinet*	14.5/50	•	•	•		•		•	100%	8/4/3
 SVTE-A-E60-CanOpen	5/15	•	•			•			90%	2/1/1
 SVTE-A-E60-EtherCAT	5/15	•	•			•	•		90%	2/1/1
 SVTE-A-E65-CanOpen	5/15	•	•			•			100%	2/1/1
 SVTE-A-E65-EtherCAT	5/15	•	•			•	•		100%	2/1/1
 SVTE-A-E65-Profinet	5/15	•	•			•		•	100%	2/1/1
 SVTE-A-E67-CanOpen	5/15				•	•			100%	2/1/1
 SVTE-A-E67-EtherCAT	5/15				•	•	•		100%	2/1/1
 SVTE-A-E67-Profinet	5/15				•	•		•	100%	2/1/1

\*Operating temperature: -40 +70°C

\*\*Operating temperature: -25 +40°C

